

Ashton Seals

General Purpose Seals



GENERAL PURPOSE SEALS

O-RINGS
O-RING CORD
BACK-UP RINGS
BONDED SEALS (COMMONLY KNOWN AS DOWTY WASHERS)
OIL SEALS
NYLON CAPTIVE WASHER (COMMONLY KNOWN AS SELON WASHERS)
RUBBER COVERED LOCK WASHERS (COMMONLY KNOWN AS SELOC WASHERS)
X-RINGS (ALSO KNOWN AS QUAD RINGS)
FEP ENCAPSULATED O-RINGS

KITS

STANDARD KITS
AUTOMOTIVE AIR CONDITIONING KITS
PLUMBERS KITS
SPlicing KITS
BONDED SEALS KITS
GREASE NIPPLE KITS
BESPOKE KITS

HYDRAULIC & PNEUMATIC SEALS

ROD SEALS
PISTON SEALS
WIPER SEALS
GUIDE RINGS
VEE PACKING SEALS
DISTRIBUTOR SEALS
U-CUP SEALS

POWER TRANSMISSION SEALS

RADIAL SHAFT SEALS
METAL FACE SEALS
V-RING SEALS
AXIAL SHAFT SEALS
AXIAL CLAMP SEALS
TRACK PIN SEALS
CASSETTE SEALS
SPEEDI SLEEVES
VR SEALS

MECHANICAL/FLUID HANDLING SEALS

METAL SPRING LOADED SEALS
METAL ENCASED PTFE SEALS
FDA APPROVED SEALS

MACHINED SEALS

VIRTUALLY UNLIMITED SEAL DESIGNS
FROM PTFE, POLYURETHANE, NBR AND FLUOROELASTOMERS

GASKETS

MANUFACTURED IN-HOUSE
FLAT CUT GASKETS DESIGNED IN A VAST RANGE OF MATERIALS
SPIRAL WOUND GASKETS
PTFE ENVELOPE GASKETS
CAM PROFILE GASKETS
RING TYPE JOINTS

GRAPHITE

GRAPHITE FOLDS
GRAPHITE TAPE
GRAPHITE REINFORCED SHEET
GRAPHITE GASKETS

LUBRICATION

GREASE GUNS
GREASE NIPPLES
GREASE NIPPLE KITS
CONNECTORS
NYLON RUBBER HOSES
OIL CANS
BUCKET PUMPS

O-Rings

Extensive stock of O-Rings in NBR, HNBR, Viton®, EPDM, FFKM, AFLAS® and Silicone as well as special materials and grades for demanding applications in the Petrochemical, Gas, Water and food industries to name but a few.

Standard sizes stocked comply with BS1806 as well as BS 4518 and DIN 3771 (metric) ranges.

O-Ring Cord

Supplied in any of the O-Ring materials and any cross section dimension from 1mm upwards. Square section cord is also available. We are able to produce vulcanised cord to specific requirements.

Back-Up Rings

To prevent seal extrusion under high pressure applications. Available in solid, split, spiral and concave type in PTFE or in 90 shore NBR.

X-Rings

Sizes to fit standard O-Ring grooves, X-Rings are ideal for reciprocating movement as they resist an O-Ring's tendency to twist or roll in the groove. Available in NBR, HNBR, Viton®, EPDM, FFKM, AFLAS® and Silicone as well as special materials and grades for demanding applications in the Petrochemical, Gas, Water and food industries to name but a few.

Extruded Profiles

Wide range of sizes and profiles from stock. Any special shape can be made to order.

Ashton Seals specialise in Seals, Gaskets, Lubrication and Anti-Vibration Machinery Mounts and supply companies at every stage in the production process. These include original equipment manufacturers, chemical processing installations, service industries, smaller distributors and stock management companies.

Viton® is a registered trademark of DuPont Dow Elastomers


AFLAS® is a registered trademark of the Asahi Glass Co. Ltd.



O-RINGS



O-RING CORD



BACK UP RING



X-RINGS



EXTRUDED PROFILES